

## Yellow/Green Striped, flame retardant, polyolefin heat shrink tubing.

Flexible, single thin wall, 2:1 ratio, low shrinkage temperature. RoHS Compliant.

### Typical Features & Applications

For ground identification in electrical, industrial and commercial applications. General insulation, mechanical protection and identification of wire, cables and harnesses.

### Standard Colour: Yellow/Green Striped

For general coloured heat shrink refer to *FiniTUBE C* range.

### Technical Features

Minimum Shrinkage temperature	+70°C
Full recovery temperature	+100°C
Operating temperature	-55°C to +135°C
Shrinkage ratio	2:1
Tensile strength	14 Mpa
Dielectric strength	20 kV/mm
Standards	UL224 VW-1 125°C 600V. SAE-AMS-DTL-23053/5 RoHS Compliant.

### Packaging

Bulk spools. Cut lengths and customised packaging available on request.

Also in standard *MiniSPOOL*, *MiniPACK* and *MiniKIT* cut length pre-packs.

### Standard Sizes and Spool Quantities

Part Code	SIZE Inch (nom)	SIZE mm	Supplied Internal Diameter (min)	Shrunk Internal Diameter (max)	Shrunk Wall Thickness (nom)	Quantity Bulk Spool (m)	Supplied Form (nom)
CYG-1/200	3/64	1.0	1.2	0.6	0.33	200	Round
CYG-1.5/200	1/16	1.5	1.6	0.8	0.36	200	Round
CYG-2.5/200	3/32	2.5	2.4	1.2	0.44	200	Round
CYG-3/200	1/8	3.0	3.2	1.6	0.44	200	Round
CYG-5/100	3/16	5.0	4.8	2.4	0.56	100	Round
CYG-6/100	1/4	6.0	6.4	3.2	0.56	100	Round
CYG-10/100	3/8	10.0	9.5	4.8	0.56	100	Flat 17mm
CYG-13/50	1/2	13.0	12.7	6.4	0.65	50	Flat 22mm
CYG-20/50	3/4	20.0	19.1	9.5	0.80	50	Flat 33mm
CYG-25/50	1	25.0	25.4	12.7	0.90	50	Flat 41mm
CYG-40/50	1-1/2	40.0	38.1	19.1	1.02	50	Flat 67mm
CYG-50/50	2	50.0	50.8	25.4	1.02	50	Flat 83mm
CYG-80/30	3	80.0	76.2	38.1	1.20	30	Flat 130mm
CYG-100/30	4	100.0	101.6	50.8	1.30	30	Flat 158mm

Customers should test the suitability of the products for their particular application.  
Select the largest size that will shrink down over the component to be covered.  
Full details of test methods, values and full technical data sheets are available upon request.  
All information is believed to be correct at time of publication and we reserve the right to make changes without prior notice.

Other sizes can be manufactured to order subject to minimum order quantities.  
All dimensions in millimetres unless stated otherwise.