

Special textured non-slip heat shrink tubing.
Flexible, single thin wall, low shrinkage temperature.

Typical Features & Applications

Manufactured from a specially formulated polymer which has undergone a surface treatment that provides a non-slip textured finish. Ideal for use as grips on sports equipment including racquets and fishing rods, health equipment, and tool/machinery handles.

Standard Colour: Black, Blue, Red, Yellow, Green

Technical Features

Minimum shrinkage temperature	+70°C
Full recovery temperature	+105°C
Operating temperature	-55°C to +105°C
Shrinkage ratio	2:1
Tensile strength	10.4 Mpa
RoHS	Compliant



Packaging: Individual Lengths

Standard Sizes and Lengths

Part Code	SIZE mm	Supplied Internal Diameter (min)	Shrunk Internal Diameter (max)	Shrunk Wall Thickness (nom)	Length m
NSH-20-*/1.6	20.0	20.0	11.0	0.90	1.6
NSH-25-*/1.6	25.0	25.0	14.5	1.00	1.6
NSH-30-*/1.6	30.0	30.0	17.5	1.20	1.6
NSH-40-*/1.6	40.0	40.0	23.0	1.20	1.6
NSH-50-*/1.0	50.0	50.0	28.0	1.25	1.0

Customers should test the suitability of the products for their particular application.
Select the largest size that will shrink down over the component to be covered.
Full details of test methods, values and full technical data sheets are available upon request.
All information is believed to be correct at time of publication and we reserve the right to make changes without prior notice.
All dimensions in millimetres unless stated otherwise.

*** denotes colour: Black (BLK), Blue (BLU), Red (RED), Yellow (YEL), Green (GRN)**
To order add the colour required to the part code. eg: NSH-10-BLK/1.6-5

Also available in sizes from 10mm subject to minimum order quantities.