

TECHNICAL FEATURES SELECTION GUIDE

FinISHRINK	<u>C</u>	<u>CLR</u>	<u>CYG</u>	<u>CX3</u>	<u>CTW</u>	<u>CDW</u> <u>3X</u>	<u>CDW</u> <u>4X</u>	<u>SHF</u>	<u>SLS</u>	<u>CM</u>	<u>CM</u> <u>X3</u>	<u>CM</u> <u>X4</u>	<u>SDR</u>	<u>CK</u>	<u>SV</u>	<u>SPTFE</u>	<u>SB</u>	<u>NSH</u>	<u>M</u>
General purpose	✓	✓		✓															
UL approved 125C	✓	✓		✓	✓	✓	✓							✓	✓				
MIL spec 135C			✓							✓	✓	✓	✓		✓	✓			
Flame retardant	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓		✓			
2:1 shrink ratio	✓	✓	✓		✓			✓	✓	✓			✓	✓	✓				
3:1 shrink ratio				✓		✓					✓								✓
4:1 shrink ratio							✓					✓							
Earth identification			✓																
Clear		✓				✓								✓		✓			
Black	✓			✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓			✓	✓
Colours	✓					✓												✓	
Ultra thin wall					✓														
Adhesive lined						✓	✓												
Halogen free								✓	✓								✓		
Low smoke								✓											
Low shrink temperature									✓										
High temp 150°C													✓						
High temp 175°C														✓					
High temp 200°C															✓				
High temp 260°C																✓			
Diesel resistant													✓						
Fuel resistant													✓	✓	✓				
Hydraulic/Oil resistant													✓		✓				
Chemical resistant														✓		✓			
Solvent resistant														✓	✓				
Acid resistant															✓				
Medium voltage busbar																	✓		
Non-Slip textured finish																		✓	
Medium wall																			✓
High electrical insulation																✓			

Note: This is a guide only. Please refer to the product data sheets for full specifications. Certain products are manufactured to order and are subject to a minimum order quantity. Please contact us for details.